


PIN NO.	PIN NAME	PIN NO.	PIN NAME
1	VLED+	26	G1
2	VLED+	27	GO
3	VLED-	28	R7
4	VLED-	29	R6
5	GND	30	R5
6	VCOM	31	R4
7	DVsp	32	R3
8	MODE	33	R2
9	DE	34	R1
10	VS	35	R0
11	HS	36	GND
12	B7	37	DCLK
13	B6	38	GND
14	B5	39	L/R
15	B4	40	U/D
16	B3	41	VGH
17	B2	42	VGL
18	B1	43	AVD
19	B0	44	RESET
20	G7	45	NC
21	G6	46	VCOM
22	G5	47	DITHB
23	G4	48	GND
24	G3	49	NC
25	G2	50	NC

If:140mA(TYP) Vf:8.7V(MIN)9.6V(TYP)10.5V (MAX)



Backlight 21LED Circuit

1	Operating Voltage:	VDD=3.3V typ.
2	Resolution:	800RGB*480
3	Color:	16.7M
4	Interface:	24 BIT RGB
5	Display type:	Transmissive
6	Viewing Direction:	12:00
7	Operating Temp:	-20°C~70°C
8	Storage Temp:	-30°C~70°C
9	Driver IC:	EK9713CA,EK73002AB
10	CTP Driver IC:	
11	LCM Luminance(cd/m2):	320(MIN),400(TYP)
12	Unspecified tolerance:	±0.3